



P.C.B LAYOUT

Material: PA46+30%GF (BEIGE)
 Insulation: Phosphor bronze
 Terminal: Tin plated
 Finish: Tin plated

Specifications:
 Current rating: 1A AC, DC
 Voltage rating: 50V AC, DC
 Contact resistance: Initial value/20mΩ max
 After environmental testing/40mΩ max

Insulation resistance: 100MΩ min
 Withstanding voltage: 500V AC/minute
 Temperature range: -25°C - +85°C

POLES	A ±0.08	B ±0.08	C ±0.05
4	6.00	4.65	3.00
5	7.00	5.65	4.00
6	8.00	6.65	5.00
7	9.00	7.65	6.00
8	10.00	8.65	7.00
9	11.00	9.65	8.00
10	12.00	10.65	9.00
11	13.00	11.65	10.00
12	14.00	12.65	11.00
13	15.00	13.65	12.00
14	16.00	14.65	13.00
15	17.00	15.65	14.00

TOLERANCE TABLE		
.0	±0.20	
.00	±0.10	
.000	±0.05	

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE: SH1.0-XP SMT 贴片
LXF	2008-09-03	CLIENT P/N: /
		UNIT: mm
		SCALE: free
		FILE NO. CKM-SH1.0-000004
		REV. A