



RECOMMEND P. C. BOARD LAYOUT
PCB TOLERANCE: ± 0.05 (TOP VIEW)

SPECIFICATIONS

Current Rating: 1.5 Amps
 Withstanding Voltage: AC 400V
 Insulation Resistance: 800 M Ω Min
 Contact Resistance: 20m Ω Max
 Operation Temperature: -40° to +105°
 Insulator Material: Polyester (UL94V-0)
 Standard: 6T
 Contact Material: Brass
 Contact Plating: Au or Sn over 40u" Ni
 Max. Processing Temp: 230° C for 30-60 seconds
 (260° C for 10 seconds)

| | | | | | | | | | | | |
|-----------------|------------|-------|--|--|-----------------|------------|------|-----------|----------|---|-------|
| APPROVED: | | DATE: | | Ckmtw 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRY CO., LTD | | | | | | | |
| | | | | | | | | | CHECKED: | | DATE: |
| DRAWN: | | DATE: | | 310-2SMT-XP | | | | | | | |
| | | | | LYF | | 2012-01-13 | | PROD. P/N | | / | |
| TOLERANCE TABLE | | | | UNIT | mm | SCALE | free | | | | |
| .0 | ± 0.30 | | | FILE NO. | Ckmtw-310-00014 | REV. | A | JL01 | | | |
| .00 | ± 0.20 | | | | | | | | | | |
| .000 | ± 0.05 | | | | | | | | | | |