



8P~14P Without Guideway  
16P~40P With Guideway  
Scale: 1/0.5



Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
2*02	2.00	6.00	2*12	22.00	26.00
2*03	4.00	8.00	2*13	24.00	28.00
2*04	6.00	10.00	2*14	26.00	30.00
2*05	8.00	12.00	2*15	28.00	32.00
2*06	10.00	14.00	2*16	30.00	34.00
2*07	12.00	16.00	2*17	32.00	36.00
2*08	14.00	18.00	2*18	34.00	38.00
2*09	16.00	20.00	2*19	36.00	40.00
2*10	18.00	22.00	2*20	38.00	42.00
2*11	20.00	24.00			

**Specifications:**  
 Current rating: 3A AC/DC.  
 Voltage rating: 250V AC/DC  
 Temperature range: -25°C~+85°C.  
 Contact resistance: ≤10mΩ Max.  
 Insulation resistance: ≥1000MΩ Min.  
 Withstanding voltage: 800V AC/minute.  
 Material: PA4T. UL94V-0.

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:

DATE:

CHECKED:

DATE:

DRAWN:

DATE:

LXF

2019-05-07

深圳市灿科盟实业有限公司  
 CHANKLEMENT INDUSTRY CO., LTD

TITLE:  
 2016S-2\*XP 直针座

PART. NO.		SCALE		REV.	A /
UNIT	mm	free	free		
FILE NO.	Chantw-2016-0001	REV.	A /		