



PC Board Layout
Component Side Shown

NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE ∅0.46mm.
- 3.PLATING :GOLD PLATING OVER NICKEL.

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOMHS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC.
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50HZ 1MIN.

MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1.STORAGE :-40°~+85°T
- 2.OPERATION :0° TO 70° C.

APPROVED:	DATE:	TITLE:	CLIENT P/N	UNIT	SCALE	REV.	HY04
CHECKED:	DATE:	RJ45-8P/8C TAB-Down H=15.1 全塑 黑色 弯插 带灯	R-RJ45R08P-A012	mm	free	A	
DRAWN:	DATE:	客户名称: 深圳市灿科盟实业有限公司					
SXA	2019-06-21	客户名称: CHANKEMENG INDUSTRYCO., LTD					
TOLERANCE TABLE							
.0	±0.30						
.00	±0.20						
.000	±0.05						