



PC Board Layout  
Component Side Shown

NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
- 2 CONTACT MATERIAL
- 3 PLATING
- ELECTRICAL:
- 1 VOLTAGE RATING
- 2 CURRENT RATING
- 3 CONTACT RESISTANCE
- 4 INSULATION RESISTANCE
- 5 DIELECTRIC WITHSTANDING RESISTANCE

MECHANICAL:

- 1 DURRABILITY
- 2 PCB RETENTION PRE-SOLDER

ENVIRONMENTAL:

- 1 STORAGE
- 2 OPERATION

:125 VAC RMS

:15 AMP.

:30 MILLIONHMS MAX.

:500 MEGOHMS MIN @ 500V DC.

:1000V AC RMS 50HZ MIN.

:750 CYCLES MIN.

:1 LB MIN.

: -40°~+95°

: 0? TO 70?.

TOLERANCE TABLE	
.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE:	CLIENT P/N	SCALE	REV.	HY04
CHECKED:	DATE:	RJ45-8P/8C 1*2 TAB-Down H=20.57 全塑 弯插	R-RJ45R08P-A201	free	A	
DRAWN:	DATE:	深圳市灿科盟实业有限公司				
SXA	2019-06-21	CHANKEMENG INDUSTRYCO., LTD				