



PC Board Layout
Component Side Shown

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

NOTES:

MATERIAL :

- 1 HOUSING MATERIAL : GLASS FILLED POLYESTER U94V-0
- 2 CONTACT MATERIAL : PHOSPHOR BRONZE φ0.45mm
- 3 PLATING : GOLD PLATING OVER NICKEL
- 4 SHIELD : 0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.

ELECTRICAL:

- 1 VOLTAGE RATING : 125 VAC RMS
- 2 CURRENT RATING : 15 AMP
- 3 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4 INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC.
- 5 DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50Hz 1MIN.

MECHANICAL:

- 1 DURABILITY : 750 CYCLES MIN.
- 2 PCB RETENTION PRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

- 1 STORAGE : -40°~+85°
- 2 OPERATION : 0° TO 70°C

APPROVED:	DATE:				
CHECKED:	DATE:	TITLE: RJ45-8P/8C TAB-Down H=18.4 弯插 带屏蔽 脚后3.05			
DRAWN:	DATE:	CLIENT	P/N	SCALE	REV.
SXA	2018-07-17	R-RJ45R08P-B002	mm	Free	A
		FILE NO.	Ckmtw-RJ45-0126		HY04