



NOTES:

MATERIAL:

- 1.HOUSING MATERIAL : GLASS FILLED POLYESTER U94V-0.
- 2.CONTACT MATERIAL : PHOSPHOR BRONZE φ0.45mm.
- 3.PLATING : GOLD PLATING OVER NICKEL.
- 4.SHIELD : 0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.

ELECTRICAL:

- 1.VOLTAGE RATING : 125 VAC RMS.
- 2.CURRENT RATING : 15 AMP.
- 3.CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE : 500 MEGOHMS MIN @ 50V DC.
- 5.DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50HZ. MIN.

MECHANICAL:

- 1.DURABILITY : 750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER: 1 LB MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°~+85°
- 2. OPERATION : 0° TO 70°

TOLERANCE TABLE	
	0
±0.30	
±0.20	
±0.05	
.000	

APPROVED:	DATE:	<b>C</b> 深圳市灿科盟实业有限公司 kmtw CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
ZYJ	2017-02-19	RJ45-8P/8C TAB-Down H=21.2 弯插 带屏蔽 无灯 无弹 脚后3.05
		PART. NO. R-RJ45R08P-B005
		UNIT mm SCALE Free
		FILE NO. Ckmtw-RJ45-0178 REV. A HY04