



PC Board Layout
Component Side Shown

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
- 2 CONTACT MATERIAL
- 3 PLATING
- 4 SHIELD
- 5 LED

ELECTRICAL:

- 1 VOLTAGE RATING :125 VAC RMS.
- 2 CURRENT RATING :15 AMP
- 3 CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4 INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC.
- 5 DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

- 1 DURRABILITY :750 CYCLES MIN.
- 2 PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1 STORAGE : -40°~+85°
- 2 OPERATION : 0° TO 70°

APPROVED: DATE:

CHECKED: DATE:

DRAWN: DATE:

SXA 2018-10-28

深圳市灿科盟实业有限公司
Ckmtw CHANKLEMENT INDUSTRYCO., LTD

TITLE:

RJ45-8P/8C 双层 2*1 弯插 带屏蔽 双带灯 无弹片

P/N R-RJ45R08P-C200

UNIT	mm	SCALE	Free	REV.	A
FILE NO.	Ckmtw-RJ45-0200	REV.	A	HY04	