



PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
 - 2 CONTACT MATERIAL
 - 3 PLATING
 - 4 SHIELD
- ELECTRICAL:
- 1 VOLTAGE RATING
 - 2 CURRENT RATING
 - 3 CONTACT RESISTANCE
 - 4 INSULATION RESISTANCE
 - 5 DIELECTRIC WITHSTANDING RESISTANCE
- MECHANICAL:
- 1 DURABILITY
 - 2 PCB RETENTION PRE-SOLDER
- ENVIRONMENTAL:
- 1 STORAGE
 - 2 OPERATION

- :125 VAC RMS
- :15 AMP
- :30 MILLIOHMS MAX.
- :500 MEGOHMS MIN @ 500V DC
- :1000V AC RMS 50HZ MIN
- :750 CYCLES MIN
- :1 LB MIN
- : -40°C~+85°C
- : 0°C TO 70°C

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:

DATE:

CHECKED:

DATE:

DRAWN:

DATE:

ZYJ

2016-10-19

深圳市灿科盟实业有限公司
Ckmtw CHANKLEMENT INDUSTRYCO., LTD

TITLE:

RJ45-8P/8C 2*4P 八胞胎 弯插 带屏蔽 带灯 带弹片
(5)JB-2X4-8P8C-LED-S-E

PART. NO. R-RJ45R08P-C802

UNIT	mm	SCALE	Free	REV.	A	HY04
FILE NO.	Ckmtw-RJ45-0113					